


Pick your Extension Card

Flexy Extension Card - 3 USB Ports

This Flexy extension card increase the connectivity capability of the Ewon Flexy with 3 USB ports.

The Flexy USB card provides OEM and system integrators an additional way to connect to their industrial devices. Many small automation devices have seen their programming port which in the past worked through serial connectivity be replaced by USB connectivity. The 3 ports USB card is a 2.0 version at full speed and can pilot up to 10 USB connections.

It is compatible with the Ewon Flexy 10x series, 20x series and 205.



Technical Characteristics

Leds	4 leds:1 global status, 1 for each port status.
Connector	Type A female
Current limit	Each port has its own 500mA current limit . Global current limit on the board is 500mA

Port activation	All ports will be enabled/disabled together
Isolation	Earth GND isolation is limited to 500V due to USB connector design
Operating temp.	-25 to +60°C
Marking	CE, cURus, FCC, UKCA

Certifications

CE	Compliant with : EMC directive 2014/30/EU (Immunity: industrial level) ROHS2 2011/65/EU directive with amendment 2015/863 REACH regulation
UKCA	Compliant with: Electromagnetic Compatibility Regulations 2016; Radio Equipment Regulations 2017; The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012.
FCC/IC	This product complies with the Part 15 of the FCC rules
Safety	The product fulfils the requirements of: EN 62368-1:2014 + A11:2017 UL 62368-1 Second Edition CAN/CSA C22.2 No. 62368-1-14 Second Edition EN 60950-1:2006 + A1:2010 +A11:2009 + A12:2011 + A2:2013

Ordering Information

ORDER CODE: FLB3601_00

MODEL NUMBER : 02601

WARRANTY: 3 years

For purchasing instructions and terms and conditions, see: → [How to buy](#)

Do you want the advice of our experts? → [Contact Us](#)